CoreDown 125

CDL Series

High-performance recessed LED downlight designed for commercial, residential, hospitality and general architectural applications. Featuring a slim heat-sink body, high-transmittance PC optics and broad 60° light distribution, CoreDown 125 provides efficient, uniform illumination with CRI >90 and IP65 protection



20W	90CRI	50,000h	90 lm/W
Power	Rendering	Lifespan	Efficacy


Technical Specifications


Color Temperature	3000K
Input Voltage	220–240V AC
Material	ADC12 Aluminium + PC
Finish	Texture White/ Texture Black
Mounting	Ceiling Recessed
Operating Temp	-20°C to +50°C
Control Options	On/Off, Triac, 1–10V, DALI
Accessories	Honeycomb Louver


Dimensions


Fixture: Ø135 mm x 65 mm H
Cutout: Ø125 mm
Beam Angles: 60°

Dimensions










Light Distribution & Beam diagram



Ordering Code

Series		Body/ Size		Wattage		Color Temp		Beam Angle °		Control		Protection
CDL 125	–	______	–	______	–	______	–	______	–	______	–	__________
CoreDown 125 (CDL 125)		Ø125 mm Cut-out (125)		20W		3000K (930)		60°		DALI		IP65

Compliance

•IP65 rated • CRI >90 • DALI-2 compatible