CleanPanel CR – High Body

CR Series

High-performance IP65 recessed LED cleanroom panel designed for uniform, low-glare illumination in healthcare, laboratory, cleanroom and other controlled environments. Featuring CRI >90, UGR <19 and a robust IK08 construction, the luminaire provides reliable visual comfort with DALI control for professional lighting applications



40W	90+ CRI	50,000h	105 lm/W
Power	Rendering	Lifespan	Efficacy

Technical Specifications

Color Temperature	2700K / 3000K / 3500K / 4000K
Input Voltage	220–240V AC, 50/60Hz
Material	Aluminium Frame + Steel Back Plate + Glass Cover
Finish	White – RAL 9010
Mounting	Ceiling Recessed
Operating Temp	-20°C to +50°C
Control Options	On/Off, Triac, 1–10V, DALI
Accessories	Waterproof Driver Enclosure


Dimensions

Fixture: 595 × 595 × 40 mm

Cutout: -

Beam Angles: 120°

Dimensions








Light Distribution & Beam diagram

120°



Ordering Code

Series		Body/ Size		Wattage		Color Temp		Beam Angle °		Control		Protection
CRP	–	______	–	______	–	______	–	______	–	______	–	__________
CleanPanel (CRP)		H6060 High Body 600 × 600		40W		4000K		120°		DALI		IP65

Compliance

• CE certified • IP65 rated